

Product Data Sheet

DIN 41612 Female straight, type B/3,
Part No. 102-80004TH






Illustration similar



Perpendicular



Through Hole



Rugged

- Termination length 2.5 mm
- 10 contacts
- THTR
- performance level 2



» to product on www.ept.de



» to product group DIN 41612

Product Data Sheet

DIN 41612 Female straight, type B/3,
Part No. 102-80004TH



Technical Specifications

Basics

Specification	IEC 60603-2 (DIN 41612)
Performance Level	2
No. of Contacts	10
Termination Technology	THTR
Termination Length	2.5 mm
Board-to-Board Distance	16.85 mm
Operating Temperature Range	-55°C to +125°C

Material

Insulator Material	PA glass filled UL 94 V-0
CTI value <i>IEC 60112</i>	600
Contact Material	Copper alloy

Mechanical

Pitch	2.54 mm
Separating Force per Pin	> 0.15 N
Durability	400 mating cycles

Electrical

Operational Current	2.6 A
Contact Resistance	<20 mΩ
Clearance and Creepage	≥ 1.2 mm
Insulation Resistance	>10 ⁶ MΩ
Test Voltage	1000 V

Processing

Soldering Temperature	260°C per J-STD-020
MSL	1

Approval / Compliance

UL file	E130314
Environment	RoHS compliant


Product Data Sheet

DIN 41612 Female straight, type B/3,
Part No. 102-80004TH



Derating Diagram

Current carrying capacity DIN C (96 pins)
max. 2.6A at 20°C



Product Data Sheet


DIN 41612 Female straight, type B/3,
Part No. 102-80004TH



Options

Board Lock

Suitable for connectors with type B, C, D, E, F low profile, G low profile, M female connectors and R male connectors



Type of Insertion	Forces			Part Number	PCB Thickness
	F _m	not soldered F _h	soldered F _h		
Locked	< 20 N	> 10 N	> 25 N	102-80004THC1	1.6 mm
Under Tension	< 20 N	> 5 N	> 25 N	102-80004THC2	2.4 mm
				102-80004THC3	3.6 mm

Modifications

Available on request

- Without flange
- Special contact length
- Performance levels I + III or customer-specific
- Contact arrangement

Accessories

» DIN 41612 Coding type B and C
Part Number 104-19003

Product Data Sheet

DIN 41612 Female straight, type B/3,
Part No. 102-80004TH



Drawings

Component data for this product you can request through sales@ept.de