

# Product Data Sheet

DIN 41612 Female straight, type C/2,  
Part No. 104-90004






Illustration similar



Parallel



Perpendicular



Through Hole



Rugged

- Termination length 2.5 mm
- 16 contacts
- solder
- performance level 2



» to product on [www.ept.de](http://www.ept.de)



» to product group DIN 41612

# Product Data Sheet

DIN 41612 Female straight, type C/2,  
Part No. 104-90004



## Technical Specifications

### Basics

|                             |                         |
|-----------------------------|-------------------------|
| Specification               | IEC 60603-2 (DIN 41612) |
| Performance Level           | 2                       |
| No. of Contacts             | 16                      |
| Termination Technology      | solder                  |
| Termination Length          | 2.5 mm                  |
| Board-to-Board Distance     | 16.85 mm                |
| Operating Temperature Range | -55°C to +125°C         |

### Material

|                               |                            |
|-------------------------------|----------------------------|
| Insulator Material            | PBT glass filled UL 94 V-0 |
| CTI value<br><i>IEC 60112</i> | 200                        |
| Contact Material              | Copper alloy               |

### Mechanical

|                          |                   |
|--------------------------|-------------------|
| Pitch                    | 2.54 mm           |
| Mating Force             | < 15 N            |
| Separating Force per Pin | > 0.15 N          |
| Durability               | 400 mating cycles |

### Electrical

|                        |                      |
|------------------------|----------------------|
| Operational Current    | 2.6 A                |
| Contact Resistance     | < 20 mΩ              |
| Clearance and Creepage | ≥ 3.0 mm             |
| Insulation Resistance  | > 10 <sup>6</sup> MΩ |
| Test Voltage           | 1000 V               |

### Processing

|                       |          |
|-----------------------|----------|
| Soldering Temperature | to 260°C |
|-----------------------|----------|

### Approval / Compliance

|             |                |
|-------------|----------------|
| UL file     | E130314        |
| Environment | RoHS compliant |


# Product Data Sheet

DIN 41612 Female straight, type C/2,  
Part No. 104-90004



## Derating Diagram

Current carrying capacity DIN C (96 pins)  
max. 2.6A at 20°C



# Product Data Sheet

DIN 41612 Female straight, type C/2,  
Part No. 104-90004



## Options

### Board Lock

Suitable for connectors with type B, C, D, E, F low profile, G low profile, M female connectors and R male connectors



| Type of Insertion | Forces |                    |                | Part Number | PCB Thickness |
|-------------------|--------|--------------------|----------------|-------------|---------------|
|                   | $F_m$  | not soldered $F_h$ | soldered $F_h$ |             |               |
| Locked            | < 20 N | > 10 N             | > 25 N         | 104-90004C1 | 1.6 mm        |
| Under Tension     | < 20 N | > 5 N              | > 25 N         | 104-90004C2 | 2.4 mm        |
|                   |        |                    |                | 104-90004C3 | 3.6 mm        |

## Modifications

Available on request

- Without flange
- Special contact length
- Performance levels I + III or customer-specific
- Contact arrangement

## Accessories

» DIN 41612 Coding type B and C  
Part Number 104-19003

# Product Data Sheet

DIN 41612 Female straight, type C/2,  
Part No. 104-90004

---



## Drawings

Component data in 2D and 3D format you can download here:

[» PDF](#)

[» 3D IGES](#)

[» 3D STEP](#)

[» 3D PDF](#)