

# Product Data Sheet

Zero8 Plug X-High-Profile Shielded,  
Part No. 405-55180-51



Illustration similar



Parallel



Perpendicular



SMT



High Density



High Speed



Rugged



EMC

- Height: 8.65 mm
- Contact overlap: 1.5 mm
- 80 poles in a 0.8 mm grid
- SMT Connectivity
- EMC shielding
- Performance Level 1



» to product on [www.ept.de](http://www.ept.de)



» to product group Zero8

# Product Data Sheet

## Zero8 Plug X-High-Profile Shielded, Part No. 405-55180-51



### Technical Specifications

#### Basics

Performance Level <i>IEC 60512-9-1:2010</i>	1
No. of Contacts	80
Termination Technology	SMT
Board-to-Board Distance	13.5 mm to 21.0 mm
Operating Temperature Range	-55°C to +125°C

#### Material

Insulator Material	LCP, UL 94 V-0
CTI value <i>IEC 60112</i>	150
Contact Material	copper alloy
Plating	Above Ni
Termination area	Sn over Ni

#### Mechanical

Pitch	0.8 mm
Mating Force per Pin	≤ 0.5 N
Separating Force per Pin	≤ 0.4 N
Durability <i>IEC 60512-9-1</i>	500 insertion cycles
Coplanarity	≤ 0.1 mm
Vibration, sinusoidal <i>IEC 60512-6-4</i>	10–2000 Hz, 20 g
Contact mating problems if vibrations occur, sinusoidal <i>IEC 60512-2-5</i>	≤ 1 μs
Shock, semi-sinusoidal <i>IEC 60512-6-3</i>	50 g, 11 ms
Contact mating problems if shock occur, semi-sinusoidal <i>IEC 60512-2-5</i>	≤ 1 μs
Overmating Distance	0.8 mm
Wipe length	1.5 mm
Center offset	± 0.7 mm
Axial offset when mated (x/y)	± 0.4 mm
Angular offset	± 5°

# Product Data Sheet

## Zero8 Plug X-High-Profile Shielded, Part No. 405-55180-51



### Technical Specifications

#### Electrical

Operational Current <i>IEC 60512-5-2</i>	1.7 A per pin at 20°C (80 of 80 pins powered) 5.5 A per pin at 20°C (2 of 80 pins powered) 5.1 A per pin at 20°C (4 of 80 pins powered) 16 A at 20°C (shield powered)
Contact Resistance <i>IEC 60512-2-1</i>	≤ 20 mΩ
Clearance and Creepage	0.25 mm
Insulation Resistance <i>IEC 60512-3-1</i>	> 5 GΩ
Test Voltage <i>IEC 60512-4-1</i>	500 VAC
Data Transfer Rate	16 Gbit/s

#### Processing

Soldering Temperature <i>JEDEC J-STD-020E</i>	20–40 seconds at 260°C
MSL <i>JEDEC J-STD-020E</i>	1
Assembly	Pick and Place

#### Approval / Compliance

UL file	E130314
Environment	RoHS compliant

# Product Data Sheet

Zero8 Plug X-High-Profile Shielded,  
Part No. 405-55180-51

---



Derating Diagram

# Product Data Sheet

Zero8 Plug X-High-Profile Shielded,  
Part No. 405-55180-51

---



## Modifications

Available on request

- other pole counts
- other quality grades

## Drawings

Component data in 2D and 3D format you can download here:

[» PDF](#)

[» 3D IGES](#)

[» 3D STEP](#)

[» 3D PDF](#)